

2022

600 X 600 mm
Porcelain tiles

WOOD MATT SERIES





2009



600 X 600 mm
Porcelain tiles



2015



2014

600 X 600 mm
Porcelain tiles





2018



600 X 600 mm
Porcelain tiles



2027



600 X 600 mm
Porcelain tiles



2028



600 X 600 mm
Porcelain tiles



2029



600 X 600 mm
Porcelain tiles



2030



600 X 600 mm
Porcelain tiles



2036

600 X 600 mm
Porcelain tiles



2042



600 X 600 mm
Porcelain tiles



2044



2043

600 X 600 mm
Porcelain tiles





2048





VCERA

TILES LLP



2049



2050

600 X 600 mm
Porcelain tiles





2053



2054

600 X 600 mm
Porcelain tiles





2057



2058

600 X 600 mm
Porcelain tiles





2059



600 X 600 mm
Porcelain tiles


VCERA
TILES LLP



2066



600 X 600 mm
Porcelain tiles


VCERA
TILES LLP



2067



600 X 600 mm
Porcelain tiles



WOOD-70



600 X 600 mm
Porcelain tiles



2076

600 X 600 mm
Porcelain tiles





2077

600 X 600 mm
Porcelain tiles





2078

600 X 600 mm
Porcelain tiles



2079

600 X 600 mm
Porcelain tiles



2080

600 X 600 mm
Porcelain tiles



2081



600 X 600 mm
Porcelain tiles



2082



600 X 600 mm
Porcelain tiles



2083

600 X 600 mm
Porcelain tiles



2084

600 X 600 mm
Porcelain tiles





2085

600 X 600 mm
Porcelain tiles





2086

600 X 600 mm
Porcelain tiles





2087

600 X 600 mm
Porcelain tiles





2088



600 X 600 mm
Porcelain tiles



2089

600 X 600 mm
Porcelain tiles





2090



600 X 600 mm
Porcelain tiles



2091

600 X 600 mm
Porcelain tiles





2092



600 X 600 mm
Porcelain tiles



2093

600 X 600 mm
Porcelain tiles



Particulars	Standard as per ISO 13005/EN 176	OUR VALUE	METHOD OF TESTING
Deviation in length	± 0.50%	± 0.3%	EN 98
Deviation in Thickness	± 5%	±3%	EN 98
Sireightness Of Sides	+ 0.5%	+ 0.3%	EN 98
Rectangularity	± 0.6%	± 0.3%	EN 98
Surface Flatness	± 0.5%	± 0.3%	EN 98
Water Absorption	< 3	3 < 4	ISO 10545.3 EN 98
Mohs Hardness	> 5	> 5	EN 101
Flexural Strength	> 35 N/Sq.mm	> 39 N/Sq.mm	—
Abrasion Resistance	As specified by Manufacturer	PE 3	ISO 10545.6 EN 102
Frost Resistance	Frost Proof	Frost Proof	ISO 10534 - 11
Chemical Resistance	No Damage	No Damage	ISO 10534 - 18
Thermal Shock Resistance	No Damage	No Damage	ISO 10545 - 9
Colour Resistance	No Damage	No Damage	—
Stain Resistance	Resistance	Stain Proof	ISO 10545 - 14
Moisture Expansion	Nil	Nil	ISO 10545 - 10
Crazing Resistance	Min 2 Cycle	Min 4 Cycle	—

Note: Color shades may vary as per the variation in the printing process. All above technical specifications are provided for the reference purpose of the tile before ordering. Data is for the best case scenario. The accuracy of the information given hereon is the responsibility of the user. All rights reserved. All other trademarks and logos are the property of their respective owners. No liability is accepted for any loss or damage caused by the use of the information given hereon.

PACKING DETAIL

Size	Thickness	No. OF Tiles	Area Approx.	Weight Approx.
600x600 mm	9 mm	4 Pcs.	1.44 Sq. Mtr.	28kg.

UTILITY OF FLOOR TILES

